

## EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
S1	1	hydrocarbon with (distillation adj3 column)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/10/26 11:17
S2	2831	hydrocarbon with (distillation adj3 column)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/10/26 11:18
S3	103	hydrocarbon adj distillation adj3 column	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/10/26 11:19
S4	97	hydrocarbon adj distillation adj column	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/10/26 11:18
S5	4	S4 and simulation	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/10/26 11:18
S6	341	(hydrocarbon with (distillation adj3 column)) and simulat\$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/10/26 11:27
S7	19	(hydrocarbon with (distillation adj3 column)) same simulat\$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/10/26 11:23
S8	0	S6 and lumping	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/10/26 11:23

## EAST Search History

S9	41	S6 and lump\$5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/10/26 11:26
S10	15	(lumping adj3 method)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/10/26 11:26
S11	181	S6 not S9	USPAT	OR	OFF	2006/10/26 11:27
S12	4	S11 and constituents and (material with balance)	USPAT	OR	ON	2006/10/26 11:28

[Industry Search](#)[eLibrary](#)[eLibrary Map-based](#)[LookUpstream](#)

## SPE E&P Industry Search

SPE's Industry Search engine allows you to search E&P-related sites across the web. Enter text or keywords (including technical terminology) to describe your request, such as:

- Benefits of synthetic drilling fluid in offshore wells
- Use of nitrogen in hydraulic fracturing
- Production technologies or processes for tight gas formations or reservoirs

Avoid using numbers (see [FAQ](#)). For specific SPE papers, use [eLibrary Search](#).

constituents base lumping hydrocarbon thermodynamic  
liquid

[Help](#) [FAQs](#)

### Information Sources

☒ SPE Website ☒ eLibrary ☒ E&P Industry sites

Directories:

☐ Consultants ☐ R&D Providers ☐ Training Marketplace

### File Types

☒ web/html ☒ pdf ☒ doc ☒ ppt ☒ xls

### Search Results

Relevance

Results 1-25 of about 202

[Next](#)

90%



#### Simulation of Compositional Processes: The Use of Pseudocomponents in Equation-of-State Calculations

**SPE eLibrary**

The accuracy of the method is demonstrated by comparing phase splits, lumped mole fractions in liquid and vapor phases, and phase densities and phase viscosities obtained from a lumped fluid description with the same data as those obtained from a fully compositional description of hydrocarbon systems. Let us now consider a lumped description of the  $n$ -component system in terms of  $n$  groups, numbered  $S, 1, \dots, 11$ . To handle the minimization problem, we choose as variables the liquid mole numbers,  $n_p, h = x_{ps} f_L, s = 1$ .

90%



#### Reliable Wax Predictions for Flow Assurance

**SPE eLibrary**

The recently developed model of Coutinho is, however, based on high accuracy thermodynamic data. In order to put wax calculations on a firmer footing, Coutinho and co-workers have developed a wax model that is directly based on high-quality laboratory data for the properties of liquid and solid hydrocarbons and their mixtures [9,10]. We believe that this behaviour is an artifact of the lumped model. Lumping the non- $n$ -paraffins has virtually no effect on the wax calculations.

89%



#### Prediction of CO<sub>2</sub>/Crude Oil Phase Behavior Using Supercritical Fluid Chromatography

**SPE eLibrary**

Some uncertainty inevitably arises from the lumping of real components into Pseudocomponents, however, because the parameters required for EOS calculations ( $P_c, T_c, w, G$ ) cannot be measured directly. In order to estimate  $G$ 's using SFC, an equation is needed that relates the SFC retention-time of a hydrocarbon to its  $V_{int}$  interaction parameter with the CO<sub>2</sub> carrier fluid. One such equation is derived as follows.

Your search - **pseudo lumping author:Barroux** - did not match any articles.

Suggestions:

- Make sure all words are spelled correctly.
- Try different keywords.
- Try more general keywords.
- Try fewer keywords.
- Try your query on the entire web.

[Google Home](#) - [About Google](#) - [About Google Scholar](#)



lumping author:"Barroux"

Search

[Advanced Scholar Search](#)  
[Scholar Preferences](#)  
[Scholar Help](#)

Tip: Try removing quotes from your search to get more results.

Your search - **lumping author:"Barroux"** - did not match any articles.

Suggestions:

- Make sure all words are spelled correctly.
- Try different keywords.
- Try more general keywords.
- Try fewer keywords.
- Try your query on the entire web.

[Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2006 Google

[Web](#) [Images](#) [Video](#) [News](#) [Maps](#) [more »](#)[Go to Google Home](#)

Lumped hydrocarbon "three constituents" filetype:pdf

[Search](#)[Advanced Search](#)  
[Preferences](#)**Web**

Results 1 - 7 of 7 for Lumped hydrocarbon "three constituents" filetype:pdf. (0.95 seconds)

Tip: Try removing quotes from your search to get more results.

**[PDF] [No Job Name](#)**File Format: PDF/Adobe Acrobat - [View as HTML](#)

**lumped**-parameter or discrete descriptions of continuous. field equations, often arising from ... for which there are **three constituents**, C, O, and H or ...

maeresearch.ucsd.edu/goddard/iecr02.pdf - [Similar pages](#)

**[PDF] [Synthesis and Testing of Diethyl Carbonate as a Possible Diesel ...](#)**File Format: PDF/Adobe Acrobat - [View as HTML](#)

In general, the **lumped hydrocarbon** product distribution diagram under supercritical conditions is ... electronic properties of the **three constituents** of ...

www.osti.gov/bridge/servlets/purl/827157-XDVEtb/native/827157.pdf - [Similar pages](#)

**[PDF] [Natural Attenuation](#)**File Format: PDF/Adobe Acrobat - [View as HTML](#)

the presence of chlorinated and non-chlorinated **hydrocarbon ... lumped** temporal degradation rate constant, R is the retardation ...

www.wastenotnc.org/hwhome/RemedyRecommendation\_Seaboard.pdf - [Similar pages](#)

**[PDF] [TAM/WASP TOXICS SCREENING LEVEL MODEL FOR THE TIDAL PORTION OF THE ...](#)**File Format: PDF/Adobe Acrobat - [View as HTML](#)

Polycyclic aromatic **hydrocarbons** (PAHs) are a large class of compounds some ... First-order **lumped** degradation rate constants were incorporated into the PAH ...

www.potomacriver.org/info\_center/publicationspdf/ICPRB03-2.pdf - [Similar pages](#)

**[PDF] [Monitoring and Remediation Optimization System \(MAROS\)](#)**

File Format: PDF/Adobe Acrobat

constituents at once, but a simple file with one to **three constituents** is easier to ... The **lumped** SF value of a location provides a measure of its overall ...

www.gsi-net.com/Software/maros\_dl/MAROSManual\_2\_2.pdf - [Similar pages](#)

**[PDF] [for 6. \(06\)](#)**

File Format: PDF/Adobe Acrobat

**Three constituents** have been identified in Jupiter's ... **hydrocarbons** in the atmosphere of Jupiter can be explained. Sagan and Miller ...

ntns.nasa.gov/archive/nasa/casi.ntns.nasa.gov/19660006518\_1966006518.pdf -

[Similar pages](#)

**[PDF] [REMOVAL OF RESIN AND FATTY ACIDS FROM PULP MILL WASTEWATER STREAMS](#)**

File Format: PDF/Adobe Acrobat

The March results are unexceptional; all **three constituents** ... of the ability of sodium resinate to dissolve insoluble **hydrocarbons** in aqueous solution ...

etd.gatech.edu/theses/available/etd-01062004-132204/

unrestricted/makris\_stephen\_p\_200405\_phd.pdf - [Similar pages](#)

[Industry Search](#)[eLibrary](#)[eLibrary Map-based](#)[LookUpstream](#)

## SPE E&P Industry Search

SPE's Industry Search engine allows you to search E&P-related sites across the web. Enter text or keywords (including technical terminology) to describe your request, such as:

- Benefits of synthetic drilling fluid in offshore wells
- Use of nitrogen in hydraulic fracturing
- Production technologies or processes for tight gas formations or reservoirs

Avoid using numbers (see [FAQ](#)). For specific SPE papers, use [eLibrary Search](#).

"three constituents" lumping hydrocarbon gaseous  
products liquid first second third pseudo base components

[Help](#) [FAQs](#)

### Information Sources

☒ SPE Website ☒ eLibrary ☒ E&P Industry sites

Directories:

☐ Consultants ☐ R&D Providers ☐ Training Marketplace

### File Types

☒ web/html ☒ pdf ☒ doc ☒ ppt ☒ xls

### Search Results

Relevance

Results 1-25 of about 129

[Next](#)

83%



#### Obtaining PVT Data For Very Sour Retrograde Condensate Gas and Volatile Oil Reservoirs: A Multi-disciplinary Approach

**SPE eLibrary**

Finally, to obtain good matches on liquid densities, volume shifts on the heavier components was the third targeted tuning factor(s). This was done by assigning properties to the heaviest component which corresponded to progressively higher molecular weight pseudo components. Most of the lumping schemes suggested for developing pseudo components usually pick a carbon number that is closer to the smaller end of the range. Therefore, the second or third lowest carbon number component in a pseudo component range, is usually considered the best average.

82%



#### Simulation of Gas Condensate Reservoir Performance

**SPE eLibrary**

This paper presents a pseudoization procedure that reduces the multicomponent condensate fluid to a pseudo two-component mixture of surface gas and oil. We can think of pseudoization in terms of either lumping components or combining streams. The Mixture  $z$  might be flashed at a low pressure and temperature with liquid and gas separator products resulting. In lumping components, each pseudocomponent consists of a subset of the original  $n$  components, and none of the members of this subset are present in any of the other pseudocomponents.

82%



#### Predicting Retrograde Phenomena and Miscibility Using Equation of State

**SPE eLibrary**

Condensation and condensing-gas-drive recovery to achieve dynamic miscible displacement or multiple phenomena have important applications in NGL production and contact miscible displacement. In Table I the mixing rules for these parameters are based on different conformal solution theories of mixtures. An equation of state, such as Equation 1 with a choice of mixing rules is based on binary interactions. The parameters  $A_{ij}$ ,  $B_{ij}$ , and  $C_{ij}$  of this equation of state are derived from pure component properties while parameters  $A_{ij}$ ,  $B_{ij}$ , and  $C_{ij}$  are derived from binary data of  $i$  and  $j$ .



[Industry Search](#)

[eLibrary](#)

[eLibrary Map-based](#)

[Leak/Upstream](#)

## SPE E&P Industry Search

SPE's Industry Search engine allows you to search E&P-related sites across the web. Enter text or keywords (including technical terminology) to describe your request, such as:

- Benefits of synthetic drilling fluid in offshore wells
- Use of nitrogen in hydraulic fracturing
- Production technologies or processes for tight gas formations or reservoirs

Avoid using numbers (see [FAQ](#)). For specific SPE papers, use [eLibrary Search](#).

"three constituents" lumping hydrocarbon gaseous  
products liquid first second third pseudo base components

[Help](#) [FAQs](#)

### Information Sources

☒ SPE Website ☒ eLibrary ☒ E&P Industry sites

Directories:

☐ Consultants ☐ R&D Providers ☐ Training Marketplace

### File Types

☒ web/html ☒ pdf ☒ doc ☒ ppt ☒ xls